

# **PUMP UP**

**YOUR AUTOMOTIVE PROFITS**

You want to safely and cost effectively transfer all of your process and waste fluids. You want better pump performance at a reduced cost. You want to work with automotive professionals who know your specific challenges. We have what you need – Gusher air-operated, double diaphragm pumps.

**RELIABLE**

**EFFICIENT**

**LONG LIFE**

**EASE OF OPERATION**

**INTRINSICALLY SAFE**

## **APPLICATIONS**

- Waste Oil Transfer
- Machine Tool Lubrication
- Paint Kitchen Duties
- Filter Press Feed
- Corrosion Inhibitor Transfer
- Chroming & Painting
- Various Sump Duties



## GP2



### PERFORMANCE

**Max. Flow:**  
170.3 LPM (45 GPM\*)

**Max. Pressure:**  
8.6 Bar (125 PSI)

**Max. Size Solids:**  
3.17 mm (1/8")

**Dry Suction Lift:**  
5.8 m (19')

### SPECIFICATIONS

**Inlet / Discharge Piping:** 25.4 mm (1") / 19.1 mm (.75")

**Air Inlet:** 6.35 mm (1/4") FNPT

**Height:** 279.4 mm (11")

**Width:** 267.5 mm (10 17/32")

**Depth:** 200.8 mm (7 29/32")

**Wetted Materials:** Aluminum, Stainless Steel

**Elastomers:** Buna-N, Teflon® PTFE, Santoprene

## GP4



### PERFORMANCE

**Max. Flow:**  
306.5 LPM (81 GPM\*)

**Max. Pressure:**  
8.6 Bar (125 PSI)

**Max. Size Solids:**  
4.76 mm (3/16")

**Dry Suction Lift:**  
5.8 m (19')

### SPECIFICATIONS

**Inlet / Discharge Piping:** 38.1 mm (1 1/2") / 31.75 mm (1 1/4")

**Air Inlet:** 12.7 mm (1/2") FNPT

**Height:** 428.6 mm (16 7/8")

**Width:** 369.1 mm (14 17/32")

**Depth:** 285.8 mm (11 1/4")

**Wetted Materials:** Aluminum, Cast Iron, Stainless Steel

**Elastomers:** Buna-N, Teflon® PTFE, Santoprene

## GP8



### PERFORMANCE

**Max. Flow:**  
590.5 LPM (156 GPM\*)

**Max. Pressure:**  
8.6 Bar (125 PSI)

**Max. Size Solids:**  
6.35 mm (1/4")

**Dry Suction Lift:**  
7.0 m (23')

### SPECIFICATIONS

**Inlet / Discharge Piping:** 50.8 mm (2") / 50.8 mm (2")

**Air Inlet:** 12.7 mm (1/2") FNPT

**Height:** 669.2 mm (26 11/32")

**Width:** 404.0 mm (15 29/32")

**Depth:** 342.9 mm (13 1/2")

**Wetted Materials:** Aluminum, Cast Iron, Stainless Steel

**Elastomers:** Buna-N, Teflon® PTFE, Santoprene

## GP15



### PERFORMANCE

**Max. Flow:**  
919 LPM (242.7 GPM\*)

**Max. Pressure:**  
8.6 Bar (125 PSI)

**Max. Size Solids:**  
9.53 mm (3/8")

**Dry Suction Lift:**  
6.7 m (22.1')

### SPECIFICATIONS

**Inlet / Discharge Piping:** 76.2 mm (3") / 76.2 mm (3")

**Air Inlet:** 12.7 mm (1/2") FNPT

**Height:** 822.5 mm (32")

**Width:** 404.0 mm (15 29/32")

**Depth:** 342.9 mm (13 1/2")

**Wetted Materials:** Aluminum, Cast Iron, Stainless Steel

**Elastomers:** Buna-N, Teflon® PTFE, Santoprene



\*denotes U.S. Gallons per Minute