

Pump Performance

Air Inlet Pressure Range 30 - 90 PSI (2 - 6.1 bar)
 Fluid Pressure Range 1950 - 6500 PSI (132.6 - 442 bar)
 Max. Rec'd Cycles Per Minute . 60
 Displacement Per Cycle 113 in³ (6.9 cm³)
 Cycles Per Gallon (Liter) 2.0 (0.5)
 Flow @ 60 Cycles / Minute 5.4 GPM (20.4 lpm)
 Noise Level @ 60 Psi 88 db(A) w/66718 muffler

Pump Specifications

Lower Pump Material Carbon Steel
 Plunger Material 17-4 Stainless Steel
 Cylinder Material 400 Stainless Steel
 Air Motor 66506-B
 Motor Repair Kit 637112
 Motor Diameter 12"
 Stroke 6"
 Air Inlet 3/4" NPT(F)
 Lower Pump End Series 66475-X4D
 Lower Pump Repair Kit 637098-XXX
 Material Inlet 2" NPT(F)
 Material Outlet 1" NPT(F)
 Weight 147 lbs. (66.8 kgs.)



650963-X4D-B

Ordering

6 5 0 9 6 3 -X 4 D - B

Packings ————
 3 : Teflon
 C : UHMW-PE
 G : UHMW-PE/Leather Staggered
 P : UHMW-PE/Teflon Staggered
 R : Teflon/UHMW-PE Staggered

Accessories

Air F/R/L: 28353
 Airline Oil: 62274
 Air Motor Muffler: 66718
 Wet Sol: 66333-B
 Wall Mounts: 66542

