

Air Filter/Regulator/Lubricator

Model Number	Description	Pumps Used With	Port Size NPT	Reg. Pressure Range PSI (bar)	Max. Flow Pressure
MODULE/AIR 1000™ F/R/L					
C28123-600	Filter/Regulator/Lubricator Drop/fog-type lubrication, 20 micron filter, polycarbonate bowl w/guard.	2" & 3", air motor pumps	1/4 (F)	5-125 (.3-8.6)	13 SCFM (6 dm ³ /s)
P29122-600	Filter/Regulator Drop/fog-type lubrication, 20 micron filter, polycarbonate bowl w/guard.	2" & "N", air motors	1/4 (F)	5-125 (.3-8.5)	12 SCFM (6 dm ³ /s)
MODULE/AIR 2000™ F/R/L					
C28241-810	Filter/Regulator/Lubricator Drop/fog-type lubrication, 40 micron filter, metal bowls w/ sight glass.	4 1/4" & 6" air motor pumps	1/2 (F)	5-125 (.3-8.6)	110 SCFM (52 dm ³ /s)
P29241-610	Filter/Regulator Drop/fog-type lubrication, 40 micron filter, metal bowls w/ sight glass.	4 1/4" & 6" air motors	1/2 (F)	6-125 (.3-8.5)	140 SCFM (66 dm ³ /s)
HEAVY DUTY F/R/L					
28353	Filter/Regulator/Lubricator Drop/fog-type lubrication, 40 micron filter, polycarbonate bowl w/guard.	8", 10" & 12" air motor pumps	3/4 (F)	5-125 (.3-8.6)	75 SCFM (35 dm ³ /s)
F/R/L Assemblies					
651729	Kit Assembly Heavy-Duty FRL w/ hose & mounting bracket for installation to Two Post Ram.	8", 10", & 12" air motor pumps	3/4 (M)	5-125 (.3-8.6)	75 SCFM (35 dm ³ /s)
65940	Kit Assembly Heavy-Duty FRL w/ hose & mounting bracket for installation to Two Post Ram.	4 1/4" & 6" air motor pumps	1/2 (M)	5-200 (.3-13.8)	65 SCFM (31 dm ³ /s)



C28123-600



P29122-600



C28241-810



P29221-610

Air Line Lubricator

- 62274 **One Quart Bottle** - A high quality "EP" extreme pressure gear oil, non-detergent, rust or oxidation inhibited, with a viscosity of 700-1000 S.U.S. at 100° F.



28353