

Automatic Extrusion Guns

Model Number	Description	Pumps Used With	Port Size In. NPT	Working Pressure PSI (Bar)
651511	Flow Gun - Requires 4-way air valve to open and close. Adjusting screw varies stroke length. Secures to 1/2" diameter rod by allen screw. Aluminum body with tungsten carbide seats. Order 66541-XX Extrusion Nozzle Kit separately.	5000 (345)	3/8 NPT (F) (2) (M)	.250 (6) & 11/16-16 (2) 1/8 F PSI (138 bar) fluid pressure
651513-11-B	Flow Gun - Has air open, spring return cylinder. Requires 3-way air valve to open. Adjusting screw varies stroke length. Secures to 1/2" diameter rod by allen screw. 316 stainless steel with tungsten carbide seat. Order 66541-XX Extrusion Nozzle Kit separately.	5000 (345)	1/4 NPS (M) (M)	.093 (2.3) & 11/16-16 (F) (F) 50 (3.4) at 2000 PSI (138 bar) fluid pressure
651536-1	Snuff-Back Gun - High flow automatic dispensing gun is designed to handle high-viscosity materials. Requires a 4-way air valve to open and close.	5000 (345)	3/8 NPT (F) (2)	1/4 NPT (F) (2) (F) 50 (3.4) at 2000 PSI (138 bar) fluid pressure
651537-1	Flow Gun - Similar to 651511 except with carbon steel body and has ball seat located at material inlet and of valve seat assembly.	5000 (345)	3/8 NPT (F) (2)	3/8 18 (M) (2) 1/8 NPT (F) 50 (3.4) at 2000 PSI (138 bar) fluid pressure



651511



651513

Extrusion Gun Nozzle Kits

Model Number	Orifice Diameter	Model Number	Orifice Diameter	Model Number	Orifice Diameter
66541-XX	Extrusion Nozzle Kit - Used on manual or automatic extrusion guns. Hardened steel assembly includes nozzle and cap. 11/16-16 UN(F).				
66541-3	.031	66541-9	.093	66541-17	.172
66541-4	.046	66541-12	.125	66541-18	.187
66541-6	.063	66541-15	.156	66541-25	.250
				66541-37	.375



66541-XX

Material Filters

Model Number	Maximum Fluid Pressure PSI (Bar)	Filter Mesh	Filter Microns	Filter Inlet(s) Size (Qty) NPT	Filter Outlet(s) Size (Qty) NPT
1/4" fluid inlet/carbon steel construction					
651412	5,000 (345)	70	200	1/4-F (2)	1/4-F (3) Bottom swivel
1/2" fluid inlet/stainless steel construction (passivated)					
651422-40	6,000 (414)	40	375	1/2-F (2)	1/2-F (1)
651422-70	6,000 (414)	70	200	1/2-F (2)	1/2-F (1)
651422-100	6,000 (414)	100	149	1/2-F (2)	1/2-F (1)
1/2" fluid inlet/carbon steel construction (e-nickel plated)					
651420-40	6,000 (414)	40	375	1/2-F (2)	1/2-F (1)
651420-70	6,000 (414)	70	200	1/2-F (2)	1/2-F (1)
651420-100	6,000 (414)	100	149	1/2-F (2)	1/2-F (1)
651421-70	6,000 (414)	Dual Screens		1-8	3/4-F (1)
1" fluid inlet/carbon steel construction (e-nickel plated)					
651418-40-B	6,000 (414)	40	375	1-F (2)	3/8-F (3)
651418-70-B	6,000 (414)	70	200	1-F (2)	3/8-F (3)
651418-100-B	6,000 (414)	100	149	1-F (2)	3/8-F (3)



651412-X



651418-XX-B



651420-XX-B