

## 2-Way Solenoid/Pilot Acting Valves **P**ump Type/Size



- Normally Closed
- Brass Body
- Stainless Steel Steel
- Spring Return
- Connector Option Include CSN-30 or CHW-30

Model Number	Port Size	Cv	Voltage	2"	3"	4-1/4"	6"	8"	10"	12"
TB03EB-024-D	3/8"	4.5	24 DC	•	•					
TB03EB-120-A	3/8"	4.5	120 AC	•	•					
TB04EB-024-D	1/2"	4.5	24 DC			•	•			
TB04EB-120-A	1/2"	4.5	120 AC			•	•			
TB06EB-024-D	3/4"	12.0	24 DC					•	•	•
TB06EB-120-A	3/4"	12.0	120 AC					•	•	•

Note: See Page 39 for cable connectors.

## 2-Way Direct Acting Solenoid Valves



- Normally Closed
- Brass Body
- Stainless Steel Stem
- Spring Return
- Connector Options include CSN-30 or CHW-30, exception 1/4" valve which uses CSN or CHW.

Model Number	Port Size	Cv	Voltage	2"	3"	4-1/4"	6"	8"	10"	12"
TB022B-024-D	1/4"	.18	24 DC	•						
TB022B-120-A	1/4"	.18	120 AC	•						
TB035B-024-D	3/8"	4.0	24 DC		•	•	•			
TB035B-120-A	3/8"	4.0	120 AC		•	•	•			
TB045B-024-D	1/2"	4.0	24 DC			•	•			
TB045B-120-A	1/2"	4.0	120 AC			•	•			
TB066B-024-D	3/4"	8.6	24 DC					•	•	•
TB066B-120-A	3/4"	8.6	120 AC					•	•	•

Note: See Page 39 for cable connectors.

## 3-Way Solenoid Actuated Valves



CAT66P



MQ3728



H253SS



MQ3729

- Normally Closed
- Aluminum Body
- Spring Return
- Connector Options include CSN-30 or CHW-30 for CAT66-P, or CSN or CHW for all others

Model Number	Port Size	Cv	Voltage	2"	3"	4-1/4"	6"	8"	10"	12"
CAT66P-024-D	1/4"	.2	24 DC	•						
CAT66P-120-A	1/4"	.2	120 AC	•						
MQ3728-024-D	1/4"	1.5	24 DC		•					
MQ3728-120-A	1/4"	1.5	120 AC		•					
H253SS-024-D	3/8"	2.2	24 DC			•	•			
H253SS-120-A	3/8"	2.2	120 AC			•	•			
H254SS-024-D	1/2"	2.4	24 DC			•	•			
H254SS-120-A	1/2"	2.4	120 AC			•	•			
MQ3729-024-D	3/4"	7.5	24 DC					•	•	•
MQ3729-120-A	3/4"	7.5	120 AC					•	•	•

Note: See Page 39 for cable connectors

## Air Control Needle Valves



104104-NO2

- Composite Body
- Can be Panel Mounted
- Infinite Control Settings
- Corrosion-Resistant Stainless Steel Insert & Stem

Model Number	Port Size	Cv	2"	3"	4-1/4"	6"	8"	10"	12"
104104-NS2	1/4"		•	•					
104104-N02	1/4"		•	•					
104104-N04	1/2"	4.5			•	•			
104104-N06	3/4"	4.5					•	•	•

## Lock-Out Valves/Hasp



104174



100085

- Meets OSHA lock-out / tag-out regulations
- Installs upstream of air filter / regulator unit

Model Number	Port Size	2"	3"	4-1/4"	6"	8"	10"	12"
104253-2*	1/4"	•						
104174-2	1/4"	•	•					
104174-4	1/2"			•	•			
100085 (Hasp)	1/2"	•	•	•	•	•	•	•

\* Safety lock-out for Module-Air 1000

# Accessories



CSN-30



CHW-30

## Connectors

Model	Description
CSN	Strain relief connector for 3-way valves
CSN-30	Strain relief connector for 2-way valves and CAT66P-XXX-X Valves
CHW	Molded cable connector for 3-way valves, 36" molded leads
CHW-30	Molded cable connector for 2-way valves and CAT66P-XXX-X, 36" molded leads

## Coils

Model	Description
116218-39	22 mm, 24 VDC Coil
116218-33	22 mm, 120 VAC Coil
119378-39	30 mm, 24 VDC Coil
119378-33	30 mm, 120 VAC Coil

# Typical Installation

